



US005729613A

United States Patent [19]

Poletti

[11] Patent Number: 5,729,613
[45] Date of Patent: Mar. 17, 1998

[54] REVERBERATORS FOR USE IN WIDE BAND ASSISTED REVERBERATION SYSTEMS

[75] Inventor: Mark Poletti, Wellington, New Zealand

[73] Assignee: Industrial Research Limited, New Zealand

[21] Appl. No.: 624,547

[22] PCT Filed: Oct. 17, 1994

[86] PCT No.: PCT/NZ94/00110

§ 371 Date: Apr. 15, 1996

§ 102(e) Date: Apr. 15, 1996

[87] PCT Pub. No.: WO95/10831

PCT Pub. Date: Apr. 20, 1995

[30] Foreign Application Priority Data

Oct. 15, 1993 [NZ] New Zealand 248970

[51] Int. Cl.⁶ H03G 3/00

[52] U.S. Cl. 381/63; 84/630

[58] Field of Search 381/63, 61, 1; 84/630, DIG. 26, 707

[56] References Cited

U.S. PATENT DOCUMENTS

4,338,581	7/1982	Morgan	84/DIG. 26
4,366,346	12/1982	Dijkmans et al.	381/63
4,803,731	2/1989	Niimi et al.	381/63
5,109,419	4/1992	Griesinger	
5,131,051	7/1992	Kishinaga et al.	
5,142,586	8/1992	Berkhout	
5,247,474	9/1993	Kowaki	
5,297,210	3/1994	Julstrom	
5,530,762	6/1996	Jones et al.	381/63
5,555,306	9/1996	Gerzon	381/63
5,621,801	4/1997	Kuwimoto et al.	381/63

FOREIGN PATENT DOCUMENTS

0335468 4/1989 European Pat. Off. .

0 480 561	4/1992	European Pat. Off. .	
4022217	6/1991	Germany .	
4348399	12/1992	Japan	381/63
WO 93/23847	11/1993	WIPO .	

OTHER PUBLICATIONS

Schroeder, M.R., "Improved Quasi-Stereophony and 'Colorless' Artificial Reverberation," J. Acous. Soc. Am., vol. 33, No. 8, Aug. 1961, pp. 1061-1064.
Moorer, James A., "About This Reverberation Business," Computer Music Journal, vol. 3, No. 2, pp. 13-28.
Stautner, John; Puckette, Miller, "Designing Multi-Channel Reverberators," Computer Music Journal vol. 6, No. 1, Spring 1982, pp. 52-65.
Jot, Jean-Marc; Chaigne, Antoine, "Digital delay networks for designing artificial reverberators," Presented at the 90th Convention Feb. 19-22, 1991, Audio Engineering Society.

(List continued on next page.)

Primary Examiner—Curtis Kuntz

Assistant Examiner—Xu Mei

Attorney, Agent, or Firm—Woodard, Emhardt, Naughton, Moriarty & McNett

[57] ABSTRACT

A multi-channel reverberation system has a substantially constant multi-channel power gain at audio frequencies and comprises multiple signal inputs, one for each input channel, a number of comb filter networks connected to each signal input, each comb filter network including a feed forward stage, a cross-coupling network cross-coupling the comb filters to increase the reverberation echo density, and multiple signal outputs, one for each output channel. Preferably the feed forward stage of each comb filter provides a substantially constant multi-channel power gain at audio frequencies and the cross-coupling matrix is an orthogonal cross-coupling matrix cross-coupling a number of single channel allpass comb filters, positioned immediately before or after the delay lines, to create a multi-channel allpass comb filter with a unitary transfer function matrix at all frequencies.

3 Claims, 4 Drawing Sheets

